


CN

RAPPLON® 片基带 销售方案 2022



产品品号及命名法

命名法对艾玛拉皮带的 RAPPLON® 高性能片基带产品组的产品品号体系的结构进行了详细说明。
命名法总是与输送带的产品品号组合使用。

产品品号

每件产品均拥有独一无二的产品品号, 由 10 个字符组成:

- FB = 片基带
- XX = 底面/顶面涂层材料 (注: 聚酰胺箔片, 如 S 09 = SF)
- XXXXXX = 特定产品编号, 如 054624

GG E10.40 RRQ FG	G	G	E	10	.40	R	R	Q	FG
GG N27 RFQ	G	G	N	2.7		R	F	Q	
GG N15 FFQ HC	G	G	N	1.5		F	F	Q	HC
GG S22 LRC	G	G	S	22		L	R	C	
TG E04.12 RQ	T	G	E	4	.12		R	Q	
TT S04.12 C	T	T	S	4	.12			C	
TG P07.60 RC	T	G	P	7	.60		R	C	
TT E09.18 Q	T	T	E	9	.18			Q	
UU N16 SP5Q FG	U	U	N	1.6		S	P5	Q	FG
UU N06 RFQ HG FG	U	U	N	0.6		R	F	Q	HG FG

底面涂层材料
(带轮侧/运行侧)

顶面涂层材料
(传动侧/输送侧)

片基层材料

1% 伸长率的拉伸强度 (单位: N/mm)

弹性带6% 伸长率的拉伸强度 (单位: 1/10 N/mm)

带厚度 (单位: 1/10 mm)

带轮侧/运行侧表面处理
(对于织物未提及)

传动侧/输送侧表面处理
(对于织物未提及)

拼接/接头

补充说明

拉伸构件材料

A	芳纶布
E	聚酯
N	无片基层
P	聚酰胺纤维
S	拉伸聚酰胺箔片

涂层材料

G	橡胶
L	皮革
P	聚酰胺箔片
T	织物 (聚酯、聚酰胺或混合材料)
U	聚氨酯
V	绒头织物

表面处理

F	精细结构
L	纵向凹槽
P5	结构类型
P6	抓力表面
R	粗糙
S	光滑

补充说明

AX	ATEX 认证
FG	食品级
HC	高导电
HG	高抓力

所有 RAPLON® 高性能片基带均可防静电。
因此未特别提及。

特定伸长率 (K1% 或 K6%) 的拉伸强度

所述定伸强力/伸长率值为按照 DIN EN ISO 21181 标准运行之后, 1% 伸长率所需的动态力 (单位: N/mm); 对于非拉伸构件产品, 则为 6% 伸长率所需的 1/10 N/mm。

总厚度

在厚度为重要要求的应用中, 以 1/10 mm 表示的产品的总厚度便于进行输送带的选择。我们设定了以下应用: 纺织行业的切向输送带、辊筒驱动输送带、糊盒机输送带、卷筒纸折叠带以及制管机输送带。对于动力传动输送带, 由于厚度无影响, 所以未加标注; 而弹性输送带则由于厚度随伸长率而变化, 也未加标注。

输送带的精确厚度根据 DIN EN ISO 2286-3 标准进行测量, 可在每个参数表中找到。每件产品均设定了公差。


拼接/接头

C	ClassicSplice (经典接头)
Q	QuickSplice (快速接头)

经典



QuickSplice 快速接头



RAPPLON® QuickSplice 片基带

· 传送带

RAPPLON® 传送带技术参数

传送带类型	货号	传送带厚度 (mm)		传送带重量 (kg/m ²)	最小带轮直径 mm (20°C)	1% 伸长率的定伸强度 (N/mm)	防静电 (AS)	建议伸长率范围 (%)	工作温度范围 (°C)	底面涂层 (材料、颜色、表面结构)	顶面涂层 (材料、颜色、表面结构)	片基层 (材料)	常规库存
传送带													
GG E03.14 FFQ	54583	1.40	1.45	20	3.1	YES	0.5 - 2.0	+0 / +60	XNBR elastomer, Grey, Fine	XNBR elastomer, Grey, Fine	Polyester fabric	√	
GG E05.14 FFQ	54607	1.40	1.50	25	5.0	YES	0.5 - 2.0	+0 / +60	XNBR elastomer, Black, Fine	XNBR elastomer, Green, Fine	Polyester fabric	√	
GG E10.30 RRQ FG	54659	3.00	3.10	30	10.0	YES	0.4 - 0.6	+0 / +60	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyester fabric	√	
GG E10.40 RRQ FG	54660	4.00	4.20	40	10.0	YES	0.4 - 0.6	+0 / +60	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyester fabric	√	
GG E10.55 RRQ FG	54662	5.50	6.10	60	10.0	YES	0.4 - 0.6	+0 / +60	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyester fabric	√	
GG P01.14 FFQ	54582	1.40	1.40	15	1.0	YES	0.5 - 2.0	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Green, Fine	Polyamide fabric	√	
PG E05.12 SFQ	54630	1.20	1.20	20	5.0	YES	0.5 - 2.0	+0 / +60	Thermoplastic elastomer, Black, Smooth	XNBR elastomer, Green, Fine	Polyester fabric	√	
TG E04.12 RQ	54624	1.25	1.25	15	4.0	NO	0.5 - 2.0	+0 / +60	Polyester fabric, Green, Fabric texture	XNBR elastomer, Green, Rough	Polyester fabric	√	
TT E05.11 Q	54599	1.10	1.10	25	5.0	YES	0.5 - 2.0	+0 / +60	Polyester fabric, Black, Fabric texture	Polyester fabric, Grey, Fabric texture	Polyester fabric	√	
TT E09.18 Q	54598	1.90	1.90	25	9.0	YES	0.5 - 2.1	+0 / +60	Mixed fabric, Grey, Fabric texture	Mixed fabric, Grey, Fabric texture	Polyester fabric	√	
TT P02.12 Q	54647	1.20	1.00	10	2.0	YES	1.0 - 2.0	+0 / +60	Polyamide fabric, Black, Fabric texture	Polyamide fabric, Blue, Fabric texture	Polyamide fabric	√	
TU E04.09 RQ	54603	0.90	1.05	15	4.0	YES	0.5 - 2.0	+0 / +60	Polyester fabric, Green, Rough	Polyurethane, Black, Fabric texture	Polyester fabric	√	
UV E06.20 FQ	54559	2.00	2.10	20	6.0	YES	0.5 - 1.5	+0 / +60	Polyurethane, Royal blue, Fine	Fleece, Grey, Ground quality	Polyester fabric	√	

RAPPLON® QuickSplice 片基带

· 传动带、切向驱动带

RAPPLON® 输送带技术参数

输送带类型	货号	输送带厚度 (mm)	输送带重量 (kg/m ²)	最小带轮直径 mm (20°C)	1% 伸长率的定伸强度 (N/mm)	防静电 (AS)	建议伸长率范围 (%)	工作温度范围 (°C)	底面涂层 (材料、颜色、表面结构)	顶面涂层 (材料、颜色、表面结构)	片基层 (材料)	常规库存
传动带、切向驱动带												
GG E08.20 RRQ	54614	2.00	2.00	25	8.0	YES	0.5 - 1.5	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Blue, Rough	Polyester fabric	√
GG E15.20 RFQ	54655	2.00	2.10	25	15.0	YES	0.5 - 1.5	+0 / +60	XNBR elastomer, Grey, Rough	XNBR elastomer, Blue, Fine	Polyester fabric	√
GG E15.25 RFQ	54656	2.50	2.60	30	15.0	YES	0.5 - 1.5	+0 / +60	XNBR elastomer, Grey, Rough	XNBR elastomer, Blue, Fine	Polyester fabric	√
GG E15.30 RFQ	54657	3.00	3.30	40	15.0	YES	0.5 - 1.5	+0 / +60	XNBR elastomer, Grey, Rough	XNBR elastomer, Blue, Fine	Polyester fabric	√
GG E18.25 RFQ	54678	2.50	2.60	30	18.0	YES	0.5 - 1.5	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Blue, Fine	Polyester fabric	√
GG E18.30 RFQ	54679	3.00	3.10	40	18.0	YES	0.5 - 1.5	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Blue, Fine	Polyester fabric	√
UU A80.45 RRQ	54567	4.50	5.10	80	80.0	YES	0.3 - 1.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, black, Rough	Aramid fabric	√
UU E15.16 RFQ	54568	1.60	1.80	30	15.0	YES	0.5 - 1.5	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Black, Fine	Polyester fabric	√
UU E15.20 RFQ	54765	2.00	2.20	30	15.0	YES	0.5 - 1.5	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Black, Fine	Polyester fabric	√
UU E15.30 RFQ	54762	3.00	3.50	30	15.0	YES	0.5 - 1.5	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Black, Fine	Polyester fabric	√
UU E22.20 RRQ	54763	2.00	2.20	30	22.0	YES	0.5 - 1.5	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Black, Rough	Polyester fabric	√
UU E22.30 RRQ	54764	3.00	3.50	40	22.0	YES	0.5 - 1.5	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Black, Rough	Polyester fabric	√

RAPPLON® QuickSplice 片基带

· 弹性带

RAPPLON® 输送带技术参数

输送带类型	货号	输送带厚度 (mm)	输送带重量 (kg/m ²)	最小带轮直径 mm (20°C)	6% 伸长率的定伸强度 (N/mm)	防静电 (AS)	建议伸长率范围 (%)	工作温度范围 (°C)	底面涂层 (材料、颜色、表面结构)	顶面涂层 (材料、颜色、表面结构)	片基层 (材料)	常规库存
弹性带												
GG N08 RRQ	54262	1.50	1.40	15	0.8	YES	2.0 - 6.0	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Green, Rough	Thermoplastic elastomer	√
GG N15 FFQ	54585	1.40	1.40	15	1.5	YES	2.0 - 6.0	+0 / +60	XNBR elastomer, Black, Fine	XNBR elastomer, Black, Fine	Thermoplastic elastomer	√
GG N22 FFQ	54596	1.50	1.40	15	2.2	YES	2.0 - 6.0	+0 / +60	XNBR elastomer, Black, Fine	XNBR elastomer, Green, Fine	Thermoplastic elastomer	√
GG N22 RFQ	54263	1.50	1.40	15	2.2	YES	2.0 - 6.0	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Green, Fine	Thermoplastic elastomer	√
GG N27 RFQ	54608	1.70	1.65	15	2.7	YES	2.0 - 6.0	+0 / +60	XNBR elastomer, Black, Rough	XNBR elastomer, Blue, Fine	Thermoplastic elastomer	√
TT N20 Q	54588	1.25	1.30	20	2.0	NO	2.0 - 6.0	+0 / +60	Polyamide fabric, Green, Fabric texture	Polyamide fabric, Green, Fabric texture	Polyurethane	√
TU N20 FQ	54587	1.25	1.30	20	2.0	NO	2.0 - 6.0	+0 / +60	Polyamide fabric, Green, Fabric texture	Polyurethane, Royal blue, Fine	Polyurethane	√
UU N06 RFQ FG	54532	0.80	0.90	6	0.6	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Fine	Polyurethane	√
UU N06 RFQ HG	54564	1.10	0.90	15	0.6	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Fine	Polyurethane	√
UU N06 RFQ HG FG	54550	1.10	0.90	15	0.6	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Fine	Polyurethane	√
UU N08 RSQ FG blue	54563	0.80	0.90	6	0.8	NO	2.0 - 6.0	+0 / +60	Polyurethane, Royal blue, Rough	Polyurethane, Royal blue, Smooth	Polyurethane	√
UU N08 RSQ FG white	54543	0.80	1.00	6	0.8	NO	2.0 - 6.0	+0 / +60	Polyurethane, White, Rough	Polyurethane, White, Smooth	Polyurethane	√
UU N12 RFQ FG	54533	1.15	1.35	15	1.2	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Fine	Polyurethane	√
UU N16 RSQ FG blue	54540	1.10	1.30	20	1.6	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Smooth	Polyurethane	√
UU N16 SP5Q FG	54562	1.10	1.30	20	1.6	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Smooth	Polyurethane, Royal blue, P5 structure	Polyurethane	√
UU N16 SSQ FG	54551	1.10	1.30	20	1.6	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Smooth	Polyurethane, Royal blue, Smooth	Polyurethane	√
UU N17 RFQ FG	54534	1.50	1.80	20	1.7	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Fine	Polyurethane	√
UU N22 RFQ FG	54535	1.85	2.25	25	2.2	YES	2.0 - 6.0	+0 / +60	Polyurethane, Black, Rough	Polyurethane, Royal blue, Fine	Polyurethane	√
UV N12 FQ	54557	1.50	1.70	20	1.2	YES	0.5 - 1.5	+0 / +60	Polyurethane, Royal blue, Fine	Fleece, Grey, Ground quality	Polyurethane	√

RAPPLON® 经典片基带

· 弹性带

RAPPLON® 输送带技术参数

输送带类型	货号	输送带厚度 (mm)	输送带重量 (kg/m ²)	最小带轮直径 mm (20°C)	1% 伸长率的定伸强度 (N/mm)	防静电 (AS)	建议伸长率范围 (%)	工作温度范围 (°C)	底面涂层 (材料、颜色、表面结构)	顶面涂层 (材料、颜色、表面结构)	片基层 (材料)	常规库存
弹性带												
GG S02.11 FFC	54735	1.10	1.20	10	2.0	YES	2.0 - 3.0	+0 / +80	NBR elastomer, Grey, Fine	NBR elastomer, Grey, Fine	Polyamide foil	√
GG S02.11 RRC	54730	1.10	1.20	10	2.0	YES	2.0 - 3.0	+0 / +80	NBR elastomer, Grey, Rough	NBR elastomer, Grey, Rough	Polyamide foil	√
GG S04.14 RRC	54731	1.40	1.50	20	4.0	YES	2.0 - 3.0	+0 / +80	NBR elastomer, Grey, Rough	NBR elastomer, Grey, Rough	Polyamide foil	√
GG S04.30 RRC FG	54783	3.00	3.10	25	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyamide foil	√
GG S04.30 RRC green	54273	3.10	2.90	30	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S04.40 RRC FG	54784	4.00	3.10	30	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyamide foil	√
GG S04.40 RRC green	54164	4.00	4.10	30	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S06.30 RRC FG	54780	3.00	3.30	30	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyamide foil	√
GG S06.30 RRC	54274	3.00	3.30	30	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S06.40 RRC FG	54781	4.00	4.40	40	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyamide foil	√
GG S06.40 RRC	54145	4.00	4.40	40	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S06.50 RRC	54275	5.00	5.50	50	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S06.55 RRC FG	54782	5.50	6.00	60	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Grey, Rough	Polyamide foil	√
GG S06.60 RRC	54276	6.00	6.80	60	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S06.70 RP6C	54790	7.00	6.50	90	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	NBR elastomer, Light blue, P6 Super grip	Polyamide foil	√
GG S07.30 RRC	54243	3.00	3.40	40	7.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Blue, Rough	TNBR elastomer, Blue, Rough	Polyamide foil	√
GG S09.30 RRC	54736	3.00	3.50	60	9.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Blue, Rough	TNBR elastomer, Blue, Rough	Polyamide foil	√
GG S11.50 RRC	54278	5.00	5.70	60	11.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Blue, Rough	TNBR elastomer, Blue, Rough	Polyamide foil	√
PP S04.14 SSC	54761	1.40	1.60	50	4.0	YES	2.0 - 3.0	+0 / +80	Polyamide foil, Black, Smooth	Polyamide foil, Black, Smooth	Polyamide foil	√
S09 C	54504	0.90	1.00	60	9.0	NO	2.0 - 3.0	+0 / +80	Polyamide foil, Transparent, Smooth	Polyamide foil, Transparent, Smooth	Polyamide foil	√
S27 C	58181	2.70	3.40	80	27.0	NO	2.0 - 3.0	+0 / +80	Polyamide foil, Transparent, Smooth	Polyamide foil, Transparent, Smooth	Polyamide foil	√
TT S02.10 C	54752	1.00	0.85	10	2.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Blue, Fabric texture	Polyamide fabric, Blue, Fabric texture	Polyamide foil	√
TT S04.12 C	54751	1.20	1.15	20	4.0	NO	2.0 - 3.0	+0 / +80	Polyamide fabric, Blue, Fabric texture	Polyamide fabric, Blue, Fabric texture	Polyamide foil	√
TT S04.12 C black	54251	1.20	1.10	20	4.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Black, Fabric texture	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
TT S09.16 C	54250	1.65	1.65	60	9.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Black, Fabric texture	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
TT S15.23 C	54249	2.30	2.50	90	15.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Black, Fabric texture	Polyamide fabric, Black, Fabric texture	Polyamide foil	√

RAPPLON® 经典片基带

· 传送带

RAPPLON® 输送带技术参数

Belt type	Art. No.	Belt Thickness (mm)	Belt Weight (kg/m ²)	Min. pulley diameter mm (20°C)	Belt factor at 1% elongation (N/mm)	Antistatic (AS)	Recommended elongation from/to (%)	Thermal application range (°C)	Cover bottom side (Material, colour, surface structure)	Cover top side (Material, colour, surface structure)	Tension member (Material)	Standard Range Central Stock
-----------	----------	---------------------	----------------------------------	--------------------------------	-------------------------------------	-----------------	------------------------------------	--------------------------------	---	--	---------------------------	------------------------------

传送带

GT S04.25 RC	54705	2.40	3.90	40	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	Polyamide fabric, Steel blue, Fabric texture	Polyamide foil	
TG E12.50 FC	56421	5.00	5.00	80	11.0	YES	0.2 - 0.6	+0 / +80	Polyester fabric, Black, Fabric texture	Natural rubber, Red, Fine	Polyester fabric	√
TG E12.65 FC	56420	6.50	6.80	80	11.0	YES	0.2 - 0.6	+0 / +80	Polyester fabric, Black, Fabric texture	Natural rubber, Red, Fine	Polyester fabric	√
TG E18.20 P5C	57239	1.90	1.80	60	18.0	YES	0.2 - 0.6	+0 / +80	Polyester fabric, Transparent, Fabric texture	NBR elastomer, Green, P5 structure	Polyester fabric	√
TG P03.12 FC	54525	1.25	1.20	25	3.0	YES	0.2 - 0.6	+0 / +80	Polyamide fabric, Black, Fabric texture	XNBR elastomer, Green, Fine	Polyamide fabric	√
TG P04.20 RC	54265	2.00	2.00	25	3.8	YES	0.2 - 0.6	+0 / +80	Polyamide fabric, Black, Fabric texture	NBR elastomer, Green, Rough	Polyamide fabric	√
TG P07.29 RC	54266	2.90	3.00	50	7.0	YES	0.2 - 0.6	+0 / +80	Polyamide fabric, Black, Fabric texture	NBR elastomer, Green, Rough	Polyamide fabric	√
TG S04.12 RC	54269	1.25	1.25	20	4.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Green, Fabric texture	NBR elastomer, Green, Rough	Polyamide foil	√
TG S04.14 RC	54261	1.40	1.40	20	4.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Green, Fabric texture	XNBR elastomer, Green, Rough	Polyamide foil	√
TG S06.30 RC	54716	3.00	3.10	50	6.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Blue, Fabric texture	TNBR elastomer, Grey, Rough	Polyamide foil	√
TG S09.40 RC	54717	4.00	4.20	60	9.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Blue, Fabric texture	TNBR elastomer, Grey, Rough	Polyamide foil	
TG S09.60 RC	54718	6.10	6.80	80	9.0	YES	2.0 - 3.0	+0 / +80	Polyamide fabric, Blue, Fabric texture	TNBR elastomer, Grey, Rough	Polyamide foil	√

RAPPLON® 经典片基带

- 敷有橡胶涂层的传动带
- 传动带和切向驱动带

RAPPLON® 输送带技术参数

Belt type	Art. No.	Belt Thickness (mm)	Belt Weight (kg/m ²)	Min. pulley diameter mm (20°C)	Belt factor at 1% elongation (N/mm)	Antistatic (AS)	Recommended elongation from/to (%)	Thermal application range (°C)	Cover bottom side (Material, colour, surface structure)	Cover top side (Material, colour, surface structure)	Tension member (Material)	Standard Range Central Stock
敷有橡胶涂层的传动带												
GT S02 RC	54701	1.10	1.00	10	2.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	Polyamide fabric, Blue, Fabric texture	Polyamide foil	√
GT S04 RC	54702	1.30	1.30	20	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	Polyamide fabric, Blue, Fabric texture	Polyamide foil	√
GT S06 RC	54703	1.40	1.50	40	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	Polyamide fabric, Blue, Fabric texture	Polyamide foil	√
GT S09 FC	54704	1.90	2.10	40	9.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Blue, Fine	Polyamide fabric, Blue, Fabric texture	Polyamide foil	√
传动带和切向驱动带												
GG S04.17 RFC	54738	1.70	1.90	20	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Blue, Fine	Polyamide foil	√
GG S04.17 RRC green	54739	1.70	1.90	20	4.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	
GG S06.18 RFC	54734	1.80	1.90	40	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Grey, Rough	XNBR elastomer, Blue, Rough	Polyamide foil	√
GG S06.19 RFC green	54729	1.90	1.90	40	6.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	
GG S07.21 RRC green	54732	2.10	2.30	40	7.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	
GG S09.22 RFC	54733	2.20	2.50	60	9.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Grey, Rough	TNBR elastomer, Blue, Fine	Polyamide foil	√
GG S09.22 RRC green	54370	2.20	2.50	60	9.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S09.22 RRC black	54369	2.20	2.50	60	9.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Black, Rough	XNBR elastomer, Black, Rough	Polyamide foil	
GG S09.31 RRC green	54740	3.10	3.50	60	9.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	
GG S11.25 RRC green	54528	2.50	2.80	60	11.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S11.26 RFC	54530	2.60	3.00	60	11.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Grey, Rough	TNBR elastomer, Blue, Fine	Polyamide foil	√
GG S15.30 RRC	54748	3.00	3.50	80	15.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Grey, Rough	TNBR elastomer, Blue, Rough	Polyamide foil	√
GG S15.30 RRC green	54286	3.10	3.10	80	15.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S18.34 RRC green	54287	3.40	3.90	150	18.0	YES	2.0 - 3.0	+0 / +80	XNBR elastomer, Green, Rough	XNBR elastomer, Green, Rough	Polyamide foil	√
GG S18.40 RRC	54749	4.00	4.70	160	18.0	YES	2.0 - 3.0	+0 / +80	TNBR elastomer, Grey, Rough	TNBR elastomer, Blue, Rough	Polyamide foil	√

RAPPLON® 经典片基带

- 敷有皮革涂层的传动带
- 敷有条纹橡胶涂层的传动带

RAPPLON® 输送带技术参数

Belt type	Art. No.	Belt Thickness (mm)	Belt Weight (kg/m ²)	Min. pulley diameter mm (20°C)	Belt factor at 1% elongation (N/mm)	Antistatic (AS)	Recommended elongation from/to (%)	Thermal application range (°C)	Cover bottom side (Material, colour, surface structure)	Cover top side (Material, colour, surface structure)	Tension member (Material)	Standard Range Central Stock
-----------	----------	---------------------	----------------------------------	--------------------------------	-------------------------------------	-----------------	------------------------------------	--------------------------------	---	--	---------------------------	------------------------------

敷有皮革涂层的传动带

LL S06 C	54038	3.80	3.70	70	6.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Chrome leather, Grey, Ground quality	Polyamide foil	√
LL S09 C	54039	4.20	4.00	90	9.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Chrome leather, Grey, Ground quality	Polyamide foil	√
LT S06 C	54045	2.60	2.50	50	6.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
LT S09 C	54046	2.90	2.80	70	9.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
LT S11 C	54047	3.00	3.00	100	11.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
LT S15 C	54048	3.60	3.70	150	15.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
LT S18 C	54049	3.90	4.40	200	18.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
LT S27 C	54050	5.10	5.60	350	27.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√
LT S36 C	54051	5.90	6.60	400	36.0	YES	2.0 - 3.0	+0 / +80	Chrome leather, Grey, Ground quality	Polyamide fabric, Black, Fabric texture	Polyamide foil	√

敷有条纹橡胶涂层的传动带

GG S11 LRC	54289	3.25	3.60	80	11.0	YES	2.0 - 3.0	+0 / +80	NBR elastomer, Black, Longitudinal grooves	NBR elastomer, Green, Rough	Polyamide foil	√
GG S22 LRC	54297	4.60	4.90	220	22.0	YES	2.0 - 3.0	+0 / +80	NBR elastomer, Black, Longitudinal grooves	NBR elastomer, Green, Rough	Polyamide foil	√
GG S33 LRC	54298	5.70	6.20	310	33.0	YES	2.0 - 3.0	+0 / +80	NBR elastomer, Black, Longitudinal grooves	NBR elastomer, Green, Rough	Polyamide foil	√

笔记

随时恭候垂询, 为您提供切实可行的解决方案

... 还有其它多达150 处服务点, 敬请访问网址:
ammeraalbeltech.com

阿根廷

T +54 11 4218 2906
info-ar@ammeraalbeltech.com

澳大利亚

T +61 3 8780 6000
info-au@ammeraalbeltech.com

奥地利

T +43 171728 133
info-de@ammeraalbeltech.com

比利时

T +32 2 466 03 00
info-be@ammeraalbeltech.com

波兰

T +48 32 44 77 179
info-pl@ammeraalbeltech.com

丹麦

T +45 7572 3100
info-dk@ammeraalbeltech.com

德国

T +49 4152 937-0
info-de@ammeraalbeltech.com

法国

T +33 3 20 90 36 00
info-fr@ammeraalbeltech.com

芬兰

T +358 207 911 400
info-fi@ammeraalbeltech.com

韩国

T +82 31 448 3613-7
info-kr@ammeraalbeltech.com

荷兰

T +31 72 57 51212
info-nl@ammeraalbeltech.com

加拿大

T +1 905 890 1311
info-ca@ammeraalbeltech.com

哥伦比亚

T +57 1 893 9890
info-co@ammeraalbeltech.com

捷克共和国

T +420 567 117 211
info-cz@ammeraalbeltech.com

卢森堡

T +352 26 48 38 56
info-lu@ammeraalbeltech.com

马来西亚

T +60 3 806 188 49
info-my@ammeraalbeltech.com

美国

T +1 847 673 6720
info-us@ammeraalbeltech.com

葡萄牙

T +351 22 947 94 40
info-pt@ammeraalbeltech.com

瑞典

T +46 (0) 10 130 96 00
info-se@ammeraalbeltech.com

瑞士

T +41 55 2253 535
info-ch@ammeraalbeltech.com

斯洛伐克

T +421 255648542
info-sk@ammeraalbeltech.com

泰国

T +66 2 902 2604-13
info-th@ammeraalbeltech.com

西班牙

T +34 937 183 054
info-es@ammeraalbeltech.com

新加坡

T +65 62739767
info-sg@ammeraalbeltech.com

匈牙利

T +36 30 311 6099
info-hu@ammeraalbeltech.com

意大利

T +39 051 660 60 06
info-it@ammeraalbeltech.com

印度

T +91 44 265 34 244
info-in@ammeraalbeltech.com

英国

T +44 1992 500550
info-uk@ammeraalbeltech.com

越南

T +84 8 376 562 05
info-vn@ammeraalbeltech.com

智利

T +56 2 233 12900
info-cl@ammeraalbeltech.com

中国

T +86 512 8287 2709
info-cn@ammeraalbeltech.com

以色列

T +972 4 6371485
info-il@ammeraalbeltech.com

墨西哥

T +52 55 5341 8131
info-mx@ammeraalbeltech.com

土耳其

T +90 232 877 0700
info-tr@ammeraalbeltech.com


日本

T +81 52 433 7400
info-jp@ammeraalbeltech.com

秘鲁

T +51 1 713 0069
info-pe@ammeraalbeltech.com

我们提供专家建议、
 质量解决方案和本地服务,
 满足您在输送带方面的所有需求



常用联系方式:

Ammeraal Beltech
 P.O. Box 38
 1700 AA Heerhugowaard
 The Netherlands

T +31 (0)72 575 1212
info@ammeraalbeltech.com

ammeraal.com